

MINIZED, fuse switch disconnecter, D01, 1-pole, In: 16 A, Un AC: 230 V



| Model | |
|---|---------------------------------|
| Product brand name | MINIZED |
| Product designation | Fuse switch disconnecter |
| General technical data | |
| Number of poles | 1 |
| Size of fuse system / acc. to DIN EN 60269-1 | D01 |
| Overvoltage category | 4 |
| Voltage | |
| Surge voltage resistance / rated value | 6 kV |
| Supply voltage | |
| Current / at AC / rated value | 16 A |
| Operating voltage / at AC / rated value | 230 V |
| Protection class | |
| Protection class IP | IP20, with connected conductors |
| Dissipation | |
| Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole | 0.1 W |

Product details

Product feature / sealable Yes

Connections

Tightening torque / with screw-type terminals 2.5 ... 3 N·m

Mechanical Design

| | |
|-------------------|--------------------------|
| Height | 70 mm |
| Width | 18 mm |
| Depth | 88 mm |
| Mounting position | any, preferably vertical |
| Net weight | 67 g |

Certificates

| | |
|--------------------------|---|
| Reference code | |
| • acc. to DIN EN 61346-2 | F |
| • acc. to DIN EN 81346-2 | F |

General Product Approval

Declaration of Conformity



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SG7611-0KK16>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SG7611-0KK16>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SG7611-0KK16

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

