

Fault signal contact, 2 NO for miniature circuit breaker 5SL, 5SY, 5SP RCBO 5SU1, FI 5SV (for 5SU1 handle coupler 5ST3805-1 is required)








| Model | |
|---|-----------------------------|
| Product brand name | SETRON |
| Product designation | Fault signal contact |
| Design of the product | Mountable |
| Electrical endurance (switching cycles) / typical | 20 000 |
| Protection class IP | IP20 |
| Product details | |
| Product component | |
| • fault signal contact | Yes |
| Product extension | Fault signal contact |
| Number | |
| Number of fault signal contacts | 1 |
| Number of NC contacts | 0 |
| Number of NO contacts | 2 |
| Number of CO contacts | 0 |
| Connections | |
| Connectable conductor cross-section | 0.5 ... 2.5 mm ² |
| Tightening torque / with screw-type terminals | 0.5 N·m |

| | |
|--|-----------|
| Type of connectable conductor cross-sections / at AWG conductors | 24 ... 12 |
|--|-----------|

Mechanical Design

| | |
|--|----------------------------------|
| Height | 90 mm |
| Width | 9 mm |
| Depth | 70 mm |
| Net weight | 68 g |
| <ul style="list-style-type: none"> during operation during storage | -25 ... +55 °C -40 ... +75 °C |



Certificates

| General Product Approval | Declaration of Conformity | Test Certificates | Shipping Approval |
|--|---|--|---|
|  CCC |  UR |  VDE |  EG-Konf. |
| | | Miscellaneous |  LRS |

| other | Railway |
|-------------------------------|-------------------------------------|
| Miscellaneous | Vibration and Shock |

Further information

- Information- and Downloadcenter (Catalogs, Brochures,...)**
<http://www.siemens.com/lowvoltage/catalogs>
- Industry Mall (Online ordering system)**
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3021>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
<https://support.industry.siemens.com/cs/ww/en/ps/5ST3021>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3021
- CAX-Online-Generator**
<http://www.siemens.com/cax>
- Tender specifications**
<http://www.siemens.com/specifications>



13 | 23

